

Accurate Sensors Technologies AB3000 Infrared Thermometer For Aluminum Billet





Features:

Simple to use - no calibrations required High accuracy - (1%) in real site conditions Capable of measuring targets with variable emissivity Measures, through smoke, dust, water vapor etc. Temperature range: 300 -600°C, 572-1112°F Rugged design Full range of accessories Wide range of built-in functions

Performance:

Temperature range: 300 -600°C, 572-1112°F Emissivity range: 0.1 - 1.0 Response time: 0.1 - 10 Sec Default value: 0.5 sec Accuracy and Repeatability: +-1%

Electrical specifications:

Power supply: 24V (18 - 36V) DC 0.4A Optional outputs: 4-20 mA, 0-20 mA, 0-10 V, RS-232, RS-422, RS485, Alarms, Profibus, Profinet. Optional: Display P110 monochrome single channel Scanning System PS3000. Pointing laser source: Class II

Mechanical specifications:

Sensor overall dimensions: 273 x 127 x 113.5 mm Sensor weight: ~3.5 kg $\,$

Ambient condition:

Operating temperature range: 0°C ° +50°C Storage temperature range: -20°C ° +70°C Humidity: unlimited for the sensor-head

Optics:

Spot diameter: 10mm from a distance of 1 meter Different optics is available.

