

NEW

**DIGITAL THERMOMETER
DT301 / DT302 / DT304**

NEW

DT301 / DT302 / DT304

The DT301 / DT302 / DT304 digital thermometers accept type J, K, T or E probes to accommodate your existing process technology. Its backlight displays are easy to read, even in low-light areas. The DT302 allows you to measure two inputs simultaneously. The DT304 allows you to measure four inputs simultaneously.

- Accepts K, J, T, or E thermocouples
- Time-stamped multifunction record
- Relative function displays temperature change
- Differential temperature (DT302 / DT304)
- Temperature in °C or °F
- Large, backlit display
- Latest technology



SPECIFICATIONS

Power Supply	2x AAA Alkaline 1.5V battery
Probes	Type K, J, T or E thermocouple
Range	
Type K	-328 to 2498°F (-200 to 1370°C)
Type J	-346 to 2192°F (-200 to 1200°C)
Type T	-418 to 752°F (-250 to 400°C)
Type E	-238 to 1832°F (-150 to 1000°C)
Accuracy	+/- 0.1% reading + 1.0°F (+0.5°C)
Resolution	0.1°F, 1°F (0.1°C, 1°C)

ACCESSORIES

Standard bead probes
Air probes
Surface probes
Liquid probes
Right angle probes
Soft carrying case
Hard carrying case

INPUT OPTIONS

Model	Inputs
DT301	One
DT302	Two
DT304	Four

STANDARD

2x AAA battery
Standard bead probe, Type J